Marine Boatbuilders CO.

PO BOX 7826 WARWICK RI 02887 Telephone: 401-935-1186 FAX: 401-732-4528

E-Mail rickjr@marineboatbuilders.com

Web site www.marineboatbuilders.com

We are pleased to introduce our new 2022, 19' PUMPOUT BOAT. This is our third generation new mold. Built and designed from our eleven years of experiences building PUMPOUT boats, Work boats, and Patrol boats. Our boats are built for safety, simplicity, and stability. There is no wood in our boats, not in the hull, not in the deck, not in the transom.

• MODIFIED V HULL DESIGN

Our PUMPOUT hull bottom is concaving not convex like most hulls. This allows for maximum stability, and ease of handling. Our boat because of its design will not yaw in a following sea. The hull is constructed with a combination of hand laid woven, roving, and gun roving. All fiberglasses are "E" glass and the resin is thermo set polyester. The gelcoat is ISO NPG thermo set gelcoat, normally 1.5" thick. Our boat has a 10-degrsee dead rise at the stern, which allow the boat to plane quickly. The hull transom is a composite laminate 1.5" thick, a total of 3" thick. There is no wood in the transom.

• STRINGER SYSTEM

Our stringer system is a U channels all fiberglass state of the art system. There is no wood in our stringer system.

• Deck, Floor

The deck is constructed of a combination of hand laid woven, roving, and gun roving. Fiberglass "E" glass applied and the resin is thermostat gelcoat (white). The deck is finished with non-skid on horizontal surfaces. Our deck is self-bailing at all times; weather containment is full or empty. There is NO WOOD in our deck or floor. The floor is composet fiberglass.

MARINE BOATBUILDERS CO. PUMPOUT BOAT page, 2

The deck has seven, cleats, two chalks and running lights. All cleats, chalks, and running lights are stainless pop ups.

This lets you recess all items on the bow so that when you pull up along other boats you have less chance of damaging your boat, or the other. This is just another example of the differences between our product and others.

• FOAMED FLOTATION

Two-part thermostat foam is injected between the floor and hull in areas occupied by tank and other equipment.

• QUALITY GELCOAT

Only storm and blister resistant gelcoat is used to form the skin of each PUMPOUT boat, wide varieties of colors are available. White is our standard color included in the quote price; other color choices would be extra cost.

• FUEL TANK

The fuel tank is 30 gallons and located below the deck. Meets EPA current standards

• CONTAINMENT CELL

A built in 230 gallon fiberglass holding tank below the water line, is a standard feature on our 19' PUMPOUT BOAT. The containment cell has five layers of fiberglass that include three layers of 18 oz. Cloth. Our containment cell has three baffles. The tank is equipped with an alarm that sounds when tank is full.

• PUMP

Edson pump model 120 electric diaphragm pump.

The Edson pump that runs the sewage tank is located completely under the center console. Also under the console are intakes, and discharge pipes. Leaving the entire deck free to any trip hazards and much needed additional working space. The vent is located outside the starboard hull.

OTHER STANDARD FEATURES

•

- 1. Running lights.
- 2. center console with windshield
- 3. T-Top w/ electronics box
- 4. Stainless steel bow eye and transom tie-downs.
- 5. Two 3" scuppers.
- 6. Heavy-duty rub rail.
- 7. 1100 G.P.M. automatic bilge pump. Ritchie compass
- 8. (2) Deep cycle series battery, with (1) non-feed back battery switch.
- 9. Raw water wash down pump.
- 10. Seat in front of center console
- 11. Six pop up cleats on sides
- 12. One' pop up cleat on bow
- 13. four mushroom cleats inside of deck
- 14.pop up lights and chalks
- 15.full coast guard package
- 16. Hose Rack Stainless Steal
- 17.ST-1000 Tank Level gauge. Located under the center council.
- 18.VHF, SS mount, antenna

• SPECIFICATIONS

Overall length: 19'
Beam: 7'10"

Draft: 10" lightship

12" full load

Dead rise: 10 degrees Transom angle: 12 degrees

Approx. weight: 1,650 lbs. Lightship
HP rating: 140HP (Standard)
Freeboards: 26" forward, 20" aft.

Options:

Tow bar/Crash bar combination
Tow bar only
Crash bar only
Canvas enclosure
Pump Upgrade
Custom accessories
Engine upgrades
Electronics Package

• WARRANTY

We offer a five (6) year warranty on the hull and a 6-year warranty in the holding tank. This warranty applies as long as the boat is used as a Pumpout boat only.

- Engine: Suzuki 140HP(standard)
 - -Honda available
 - -Yamaha available